

11-1-1 SMART FIELD COMMUNICATOR (SFC)

Model No. SFC160 / SFC260

Issued: Jun. 1, 2002	Page : 11-1-2
Effective: Feb. 1, 2009	UNIT : 1000YEN

Model No. : SFC - -

Model No. Ex SFC160 -11X -XC				Selection								Option			
				I			II			III		IV	V		
				Display (Language/measuring unit)			Battery Charger		Explosion Protection		No option	Without carrying case	With carrying case		
AC100V, 50 / 60Hz	AC115 / 120V, 50 / 60Hz	AC200 / 220 / 240V, 50 / 60Hz	Non-Explosion-Protected				FM Approved Intrinsic Safety, Class I, Division 1 (Zone 0 and Zone 1), Group A,B,C and D (for SFC160 only)	FM Approved Nonincendive, Class I, Division 2 (Zone 2), Group A,B,C and D							
				*2 Model No.			1	2	3	X	S	N	X	X	C
		Model No.					0	0	0	0	15	10	0	0	8
		Basic No.*1	Price												
Smart Field Communicator (Standard type)	SFC160	165	1	English, non-SI unit			✓	✓	✓	✓	✓	✓	✓	✓	✓
			2	English, SI unit											
			3	English, SI unit set as default											
			4	English, inch/lb											
			7	Japanese, SI unit only											
Smart Field Communicator (with printer)	SFC260	187	1	English, non-SI unit			✓	✓	✓	✓		✓	✓	✓	✓
			2	English, SI unit											
			3	English, SI unit set as default											
			4	English, inch/lb											
			7	Japanese, SI unit only											

*1 SFC160 can not be modified and changed to SFC260 after delivery.

*2 Language can not be changed after delivery.