



| | |
|-----------------------|-----------|
| Client | |
| offer no.: | |
| Tag: | -/- |
| size | DN150 |
| rating | PN16 |
| orifice bore ϕd | 78,925 mm |
| pipe ID | 159,3 mm |
| dimension A | 212 mm |
| material | SS316Ti |
| quantity | 1 pcs. |

| | | |
|--|---|--|
| pipe line | medium | mounting of the flow sensor depend on the pipe line (horizontal or vertical) |
| <input checked="" type="checkbox"/> horizontal | <input checked="" type="checkbox"/> gas | <input checked="" type="checkbox"/> or <input type="checkbox"/> |
| <input type="checkbox"/> vertical | <input type="checkbox"/> gas | <input type="checkbox"/> |
| <input type="checkbox"/> up stream | <input type="checkbox"/> fluid | <input type="checkbox"/> |
| <input type="checkbox"/> down stream | <input type="checkbox"/> fluid | <input type="checkbox"/> |

| | | | |
|---|---------------------------------------|---|-----------------|
| 5 | 3-way manifold | 1 | 316L |
| 4 | range plate | 1 | 316Ti |
| 3 | pulse pipe $\phi 26,7 \times 2,87$ mm | 1 | EN10216 316Ti |
| 2 | pulse pipe $\phi 8 \times 1$ mm | 1 | EN10216 316Ti |
| 1 | orifice | 1 | ISO5167-1 316Ti |

Benennung: Compact Orifice with manifold
Type: BL405-DN150 PN16

| | | | |
|------------|---------|-----------------------|------|
| dated | name | mode | Form |
| 18.05.2010 | K.Brumm | INTRA-AUTOMATION GmbH | A4 |
| Gepr. | | Otto-Hahn-Strabe 20 | |
| Norm | | 41515 Grevenbroich | |

| | | | | |
|-------------|------------|--------------------|------|------|
| Item/modify | dated/name | drawing no.: | Rev. | page |
| | | MB-e-09-150-16-001 | 0 | 1/1 |
| Ursprung: | | Era./fir: | | |
| | | pos-Bez.: | | |